IF Biosafety Cabinets (BSC)

Biosafety Cabinet Class II/A2 BSC90,BSC120,BSC180

H14 99.99% @0.3um for ISO5 Class 100, U15 99.9995% @MPPS for ISO4 Class 10



Features

Slanted 10 degree front viewing window UV light timer with interlocking safety switch Running hours & Filter life indicator Airflow Velocity monitoring for Downflow & Exhaust airflow One piece SS304 Stainless Steel Work Area Negative pressure double-wall housing design LED Display Microprocessor Control

Designed and tested EN1822 - H14 99.99%/99.999%@0.3um HEPA Filters / IEST RP-CC-001.3 Type C ISO 14644-1 ISO5 or FS 209E Class 100 ULPA filters 99.9995%@mpps for ISO4 / Class 10

Tested and Certified to NSF/ANSI 49 Tested and Certified to EN12469





CLYDE-IFC is an ISO9001:2015 Quality Managed System. The assurance of quality products and service testing.Quality scheduling management will ensure your cabinets are recertified and serviced ontime. We will ensure your cabinets are tested according to testing procedures and methodology. All our test equipment are serviced and calibrated with traceability to the internationl standards.

Being Bizsafe Level 3 certified, we have high awareness of the importance of safety in aspects of industrial, chemical and biological safety. The safety mark which signifies our commitment to safe working practices especially in your premise.

Our engineers are either Accredited NSF49 Class II Biosafety cabinetry Field Certifier or NATA- registered laboratory laminar air flow services field certifiers. The assurance of your cabinets integrity. Our service engineers are able to provide all types of onsite servicing, maintenance, relocation, testing and re-certification services for biological safety cabinets, laminar flow work stations, clean room, HEPA filter installations and replacements.

Since 1998, we have commissioned, serviced and recertify at least or more than 15,000 units of laminar air flow cabinets, biological safety cabinets, fume hoods and cytotoxic drug cabinets, with an average of 800 cabinets or installations per year. This is only possible with our honorable supportive customers and partners.


Joseph Goh NSF49 Class II Biosafety Cabinet Field Certifier Cert. No.: 2X890-02 NATA Accredited Lab Biosafety Cabinetry Factory Certifier Nata Engrosey #1146




IF Biosafety Cabinets (BSC)

Biosafety Cabinet Class II/A2 BSC90,BSC120,BSC180

H14 99.99% @0.3um for ISO5 Class 100, U15 99.9995%@MPPS for ISO4 Class 10





Specifications

Model/ Item No	BSC90	BSC120	BSC180
Туре	Class II Type A2		
External Size (WxDxH) mm	1087x775x2265	1385x775x2295	1873x775x2220
Internal Size (WxDxH) mm	910x600x660	1210x600x660	1700x600x660
Control	7" Microprocessor Touch Screen w airflow fault alarm, filter & UV time		
Airflow Velocity m/s	0.35 +/- 25%		
Material Main Body: Work Area:	Electrogalvanised Steel with oven baked epoxy powder coating SS304 Stainless Steel		
Side and Front Window	Manual Sliding Sash with 5mm Laminated /Safety glass, Anti UV Optional: Motorised Sliding Sash		
Safety / Max Front Opening Height mm	Sash Window Safety Height 200 (8") / 470, 250mm (10")		
HEPA filter	* H14 99.99/99.999%@0.3um (Optional U15 99.9995%@0.3um)		
Noise Level dbA 1.5m	<65 dBA		
Light Intensity LUX	LED Lamps, >800-1200		
UV light	x1 20W	x1 30W	x1 40W
Internal Electrical Socket	x2 Waterproof Socket Total Load <450W		
Accessories: Gas Tap	Optional		
Floor Stand	Optional Floor Stand with levelling Castor Wheels		
Total Full Load Ampere (with outlets)	7A	7A	11A
Power Supply	Single Phase 230V / 50Hz		
Power Consumption W	500	600	900
Ground Resistance ohm		<0.10	
Net Weight kg	215	279	339
Gross Weight kg	270	340	410
Shipping Dimension mm	1240x1060x1900	1540x1080x1900	2020x1080x1900
Air Quality ISO 14644-1 / FS209E	ISO 5 Class 100 / ISO4 Class 10		
Standards Certification	EN12469 / NSF49 / CE ISO9001:2008		



CLYDE-IFC (S) PTE LTD

