V-Cell Minipleat

Secondary Filters F6 60-65% F7 80-85% F8 90-95% F9 >95% E10/E11 95%@0.3um, H13

General Characteristics

V-Cell Minipleat filters are used in all types of applications. High media area ensures very low pressure drop and enables extremely long life usage. It is proven to be low energy usage, low operating costs, long filter replacement periods. This filter is highly recommended and ultimate choice for use in all industries such electronics and injectable production, pharmaceutical production, nuclear establishments, industrial and chemical processing, hospitals and laboratories, biosafety laboratories, public and office buildings, airport airconditioning systems, oil refineries, gas turbines and plastic manufacturing.

- + Secondary Filters F6 F9 efficiencies
- + Low Resistance SemiHEPA E10,E11 and HEPA H13
- + V-Shaped Minipleat with thermoplastic separators
- + Synthetic Electrostatic anti-microbial filter media
- + Plastic Frame
- + Extremely Durable
- + Low Pressure Drop, Energy and Operating Costs

Construction

Filter Media

The filter media is 100% synthetic made from a modified melt-blown process and special process which is permanent electrostatically charged during media manufacturing as opposed to active or non-permanent charged. This tremendous incease the efficiency at 0.3-3um and ensures very low pressure drop during lifespan of filter. The gradual fibre density ensures coarse fibres upstream and fine fibres downstream giving optimum particle capture characteristic. The media is then manufactured through minipleating where plastic separators are added to give a unique pleated V configuration ensuring high media area, very low resistance and longer lifespan.

The filter is arranged in V shaped and sealed with hotmelt adhesive and is enclosed with standard plastic frame, and completes as a single header rigid cartridge filter of 12" inline depth.

The final minipleat filter is extremely durable with high compressive strength in the airflow direction. It has been tested to burst strength of 6250 Pa. The durability also ensures that there will be no damage to pleats during transportation or assembly.

The filter media is anti-microbial and is a by-product of manufacturing process and does not require the addition of any chemicals.

Optional galvanised steel or aluminium U channel for No header/Double header/ Box installations.Optional gaskets can be requested.



Description: V-Cell Minipleat Nominal Size: 24 x 24 x 12" Actual Size : 592 x 592 x 292mm

V-Cell Minipleat

Secondary Filters F6 60-65% F7 80-85% F8 90-95% F9 >95%

SemiHEPA E10/E11 95%@0.3um HEPA H13 99.99%@0.3um

Specifications

Model	V60	V80 / V90	V90 / V98	VH10	VH13
Description	V-Cell 60-65%	V-Cell 80-85% V-Cell 90-95%	V-Cell MERV15 F9>95%	V-Cell SemiHEPA MERV16 95%@0.3um	VCell HEPA 99.99%
Nominal Thickness	12"	12"	12"	12"	12"
Initial Pressure Drop at Face velocity 2.5m/s	55	66	80	91	280 @2.2m/s
ASHRAE 52.76 Average Dust Arrestance Efficiency (>5µm)	95%	99%	99%	99%	-
ASHRAE 52.1-1992 Average Dust Spot Efficiency (>1µm)	60-65%	90-95%	>95%	>99%	-
ASHRAE 52.2-2012 Range 1 (0.30-1.0um)	>35%	>75%	>85%	>95%	-
ASHRAE 52.2-2012 MERV	MERV 12	MERV 14	MERV 15	MERV 16	-
ASHRAE 52.2-2017 w App J MERV-A	-	-	MERV 14A	MERV 15A	-
PSL/DEHS/DOP @0.3um	-	-	>85%	>95%	>99.99%
EN1822 MPPS Global/ Integral Value @MPPS	-	-	-	>95%	>99.95%
Media Area m ²	19.2	19.2	19.2	19.2	28.0
Filter Class EN779 / EN1822 Class to ISO16890	M6 ePM 2.5 60%	F8 ePM 1.0 70%	F9 ePM 1.0 80%	E10/ E11 ePM 1.0 85%	H13 -

Performance data is based on ASHRAE 52.2-2012 Test method entitled "Method of Testing General Ventilation Air Cleaning Devices for Removal Efficiency by particle size,

other data provided is for comparision and information. MERV: Minimum Efficiency Reporting Value * EN1822 -Semi-HEPA E10,E11,E12, H13 Testing, Global Efficiency MPPS: Most Penetrating Particle Size (at 0.1-0.2um for particle counter). US IES RP-CC-001.3, MPPS is at 0.3um for photometer ASHRAE 52.2-2012 & 2017 MERV Range 1 of 0.3-1.0um uses KCL as aerosol. Optional ASHRAE 52.2 2017 App J not form part of standard

Dimensions

Nominal Size L x H x D inches	Actual Size L x H x D mm	Rated Air Flow cmh	Face Area m ²	Weight kg	Packing per carton		
24 x 24 x 12	592 x 592 x 292	3400	0.35	7.0	1		
24 x 20 x 12	592 x 492 x 292	2830	0.29	6.5	1		
24 x 16 x 12	592 x 391 x 292	2260	0.23	6.0	1		
24 x 12 x 12	592 x 289 x 292	1700	0.17	4.5	2		
12 x 12 x 12	289 x 289 x 292	850	0.08	3.0	4		

Plastic Frame available in 24x24, 24x20, 24x16, 24x12. Odd sizes can be custom fabricated with Galvanised Steel (Box Shaped only)

Box or No Header (NH) can be fabricated by adding additional metal header on V-cell or fabricating a separate holding frame box Optional Gaskets can be requested on downstream or upstream. V-cell can be installed in both directions, in reverse air flow.

Plastic Frame header of 22mm. Width and height dimensions are interchangeable. Tolerances of 3mm

Single Header (SH) 20mm



Technical Data

Filter Media Synthetic Polypropylene(PP) Polyester **Enclosing Frame** Polystrene 22mm Header Option: Galvanised Steel (Gi) for custom sizes

Separator Hotmelt

Sealant Hotmelt / PU

Continuous Operating Temperature 50°C **Relative Humidity** 90% Recommended Final Pressure Drop 250-375 Pa or Twice of Initial Pressure Drop Maximum Final Pressure Drop 450 Pa





CLYDE-IFC (S) PTE LTD

9 Joo Koon Road Singapore 628973 Tel: +65 6785 0700 Email: sales@clyde.sg http://www.clyde.sg